

FS 35A - Removal of Oil, Grease, Resin, Soot & Nicotine

Universal cleaning agent for all hard surfaces such as tiles, chrome, chromium steel, floor painted surfaces. Suitable for use as an industrial machine cleaner. It removes oil and grease, resin, soot and nicotine stains thoroughly.

Direction of usage:

Dilution 1:5 suitable for machine cleaning and industrial machine cleaner. Dilution 1:10 suitable for cleaning ovens, grills, steamers, tiles, chrome, chromium steel.

Dilution 1:20 suitable for floor cleaning.

- Non-flammable.
- The tensides used are biodegradable.

PH : 14
Colour : Red
Fragrance : Odourless

Frisag Asia Pte Ltd

220 Tagore Lane #01-09 S(787600) Tel: (65) 6451 0143 www.frisagasia.com

Headquarters: Frisag AG

Industriestrasse 10, 6345, Neuheim ZG Switzerland



CAUTION

Avoid contact with eyes. Do not ingest. Check for tightness of container regularly.



Irritant

Corrosive

Keep away from all food stuffs, beverages and feed.

First aid measures:

For eye contact

Flush with water for 15 minutes and if irritation persists, seek immediate medical attention.

For skin contact

Flush with cool water and if irritation persists, seek medical treatment.

If swallowed

Rinse out mouth and drink water. Seek medical treatment immediately.

Protective gloves

The glove material has to be impermeable and resistant to the product/the substance.

Material of gloves recommended: Butyl rubber, BR Natural rubber, NR Nitrible rubber, NBR Fluorocarbon rubber (Viton)

